



Submittal

VAULT® Exit Seal™

Exit Seals™ are of an aluminum or stainless steel configuration, utilizing the exclusive VAULT® SilX14™ gasket seal, designed to accommodate the appropriate size of pipe, cable, or desired penetrant. The standard gasket is rated for -25°F to +475°F.

Series 5000 Sizes: 0.25" OD to 1.90" OD **Materials:** aluminum body with threaded connection

Copper K&L				Copper ACR				Steel Schedule 40				Electrical EMT			
Qt.	CU	OD	Seal	Qt.	ACR	OD	Seal	Qt.	STEEL	OD	Seal	Qt.	EMT	OD	Seal
<input type="checkbox"/>	1/4	.375	5025	<input type="checkbox"/>	1/4	.25	5025	<input type="checkbox"/>	1/8	0.41	5025	<input type="checkbox"/>	1/2	0.706	5070
<input type="checkbox"/>	3/8	.50	5025	<input type="checkbox"/>	3/8	.375	5025	<input type="checkbox"/>	1/4	0.54	5025	<input type="checkbox"/>	3/4	0.922	5084
<input type="checkbox"/>	1/2	.625	5044	<input type="checkbox"/>	1/2	.50	5044	<input type="checkbox"/>	3/8	0.68	5070	<input type="checkbox"/>	1	1.163	5092
<input type="checkbox"/>	5/8	.75	5070	<input type="checkbox"/>	5/8	.625	5044	<input type="checkbox"/>	1/2	0.84	5084	<input type="checkbox"/>	1 1/4	1.51	5130
<input type="checkbox"/>	3/4	.875	5084	<input type="checkbox"/>	3/4	.75	5070	<input type="checkbox"/>	3/4	1.05	5092	<input type="checkbox"/>	1 1/2	1.70	5162
<input type="checkbox"/>	1	1.125	5092	<input type="checkbox"/>	1	1	5092	<input type="checkbox"/>	1	1.32	5130				
<input type="checkbox"/>	1 1/4	1.375	5092	<input type="checkbox"/>	1 1/8	1.125	5092	<input type="checkbox"/>	1 1/4	1.66	5162				
<input type="checkbox"/>	1 1/2	1.625	5130	<input type="checkbox"/>	1 1/4	1.25	5092	<input type="checkbox"/>	1 1/2	1.90	5190				

Electrical Rigid				or	Aluminum				or	Liquid-tight				or	PVC Schedule 40 & 80			
Qt.	OD	Seal		Qt.	OD	Seal		Qt.	OD	Seal		Qt.	OD	Seal				
<input type="checkbox"/>	3/8	0.70	5070	<input type="checkbox"/>	3/4	1.04/1.05	5092	<input type="checkbox"/>	1 1/4	1.645/1.66	5162							
<input type="checkbox"/>	1/2	0.83/0.84	5084	<input type="checkbox"/>	1	1.303/1.315	5130	<input type="checkbox"/>	1 1/2	1.883/1.90	5190							

Series 6000-7000 Sizes: 2.125" OD to 4.50" OD **Materials:** stainless steel flange with SilX14™ gaskets

Copper K&L				Copper ACR				Steel/PVC/Electrical Rigid Schedule 40				Electrical EMT			
Qt.	CU	OD	Seal	Qt.	ACR	OD	Seal	Qt.	STEEL	OD	Seal	Qt.	EMT	OD	Seal
<input type="checkbox"/>	2	2.125	6200	<input type="checkbox"/>	2-1/8	2.125	6200	<input type="checkbox"/>	2	2.375	6213	<input type="checkbox"/>	2	2.192	6200
<input type="checkbox"/>	2-1/2	2.625	6225	<input type="checkbox"/>	2-5/8	2.625	6225	<input type="checkbox"/>	2-1/2	2.875	6250	<input type="checkbox"/>	2-1/2	2.875	6250
<input type="checkbox"/>	3	3.125	6280	<input type="checkbox"/>	3-1/8	3.125	6280	<input type="checkbox"/>	3	3.5	7325	<input type="checkbox"/>	3	3.5	7325
<input type="checkbox"/>	4	4.125	7375	<input type="checkbox"/>	3-5/8	3.625	7346	<input type="checkbox"/>	4	4.5	7425	<input type="checkbox"/>	4	4.5	7425

Series 16000 Sizes: 4.50" OD to 15" OD **Materials:** stainless steel flange with SilX14™ gaskets

Qt.	Type	OD	Seal	Qt.	Type	OD	Seal	Qt.	Type	OD	Seal	Qt.	Type	OD	Seal
<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>			
<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>			
<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>				<input type="checkbox"/>			